

FE235

Retenedor electromagnético de 400N para montaje en superficie.

General

The FE235 is a surface mount door holder, with a Bayblend base, which offers a 400N holding force.

Magnet construction

The magnet is constructed with a pressed coil and anti-remenance pin, giving it a protection of IP54. The protection diodes are integrated into this construction.

Housing

The plastic base is manufactured from Bayblend and contains 30% PA6 glass fiber, which makes it much stronger than standard ABS. Bayblend offers high heat resistance, high impact and notched impact strength, and high stiffness and dimensional stability.

Installer friendly

- For practical ease of installation, the door holder comes complete with electrical screw terminals.
- The base is predrilled in a practical, standard format for rapid mounting.
- The door holder is supplied complete with a keeper plate, which offer angular adjustment.

Approvals

The FE235 is fully approved according to EN1155.



Details

- Low power - 1.6 W
- 400 N holding force
- Anti-remnant ejector
- Spark suppression diode and reverse polarity protection
- EN1155 approved
- Keeper plate included

FE235

Retenedor electromagnético de 400N para montaje en superficie.

Technical specifications

General

Fuerza de retención N (Newtons) 400 N

Botón de liberación No

Diodo de supresión de chispa Yes

Protección contra inversion de polaridad Yes

Eléctrico

Tipo de fuente de alimentación 24 VCC

Consumo de corriente 1.6 W

Ciclo de trabajo 100%

Físico

Dimensiones físicas 55 x 55 x 33 mm

Medioambiental

Clasificación IP IP54 (magnet)
IP42 (connection)

Estándares y regulaciones

Normativas EN1155

